

SB-540 EVERSEAL TAPE

DESCRIPTION: A solventless, high bond, heavy mass, structural grade pressure-sensitive tape. Cures immediately and remains permanently flexible.

USES:

Industries

- Automotive
- Manufacturing
- Construction

Substrates

- Metal
- Plastic
- Rubber
- Polyethylene sheeting
- Films

APPLICATION: To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

FEATURES:

- Clean alternative to brush- or gun-applied adhesives
- Replaces rivets and welds
- Excellent bond strength
- Non-hardening
- No cure time
- Solvent free, no fumes

BENEFITS:

- Less mess and quick, simple installation
- Time and cost effective
- Strong grip to a variety of surfaces
- Permanent flexibility
- Expedited production
- Safe

STORAGE: Tape should be stored at 70°F (21°C) with 50% relative humidity.

SHELF LIFE: 18 months.

CAUTION: For industrial use only.

PACKAGING: .04" thick .x .75" wide x 66' long rolls

COLOR: Amber

SPECIFICATIONS:

Tensile strength	150 psi
Elongation	1000%
Peel adhesion	44 pli
Application temperature range	50°F to 100°F (10°C to 38°C)
Functional temperature range	-30°F to 150°F (-1°C to 65°C)